



SERIES BD 7XXX

Truck brake tester BD 7426

Up to 13 t axle load, mechanic NEW 2017, PC ready | ICperform Software, New Tablet-App | 2 Speed, electromagnetic motor brake, 4 x 4, Roller 1000 mm | ASA-Livestream, 8-points-weight system

Article number: BD 7426

For articles to be ordered, see configuration.

Description

- Up to 13 t axle load, mechanic NEW 2017, PC ready
- ICperform Software, New with Tablet-App
- 2 Speed, 4 x 4
- Coated Rollers, 1000 mm
- With electromagnetic motor brake
- ASA-Livestream
- 8-points-weight system
- Fits in popular foundations

Optional accessories

- Durable sliding
- 8-points-weight system (available in bill of material in some configuration)
- Option for Tacho control
- Drive-over plates
- Weather-resistant hot-dip galvanization, steel chains
- Radio controlled air-pressure sensors
- Pit safety in different sizes

ICperform: new Software

- Intuitive and fast in use
- Optimum display of all relevant measured values
- Easy handling
- Faster brake testing
- Print and database functions
- Connection with other test devices within the test lane

ICperform Tablet-App

ICperform tablet app: measuring faster without having to get on and off the truck

- The intuitive user interface can be accessed via Android tablets operate and enable stable measured value transmission and control via the W-LAN connection - even from inside the vehicle.
- Roll resistance, ovality, braking forces per axis or wheel, left-right comparison or pressure values, all data are displayed in real time and visually intuitive
- Working with Beissbarth's ICperform tablet app speeds up the process and eliminates unnecessary entry and exit from the vehicle.

New! ICperform tablet app from Google Play

- The app is available at play.google.com. Download it to your tablet and try the features for up to 30 days free of charge. You can obtain your license for the ICperform tablet app (order number 1 691 810 756) directly from the Beissbarth hotline.

Carrying out brake tests easily and quickly with the software ICperform tablet

- Data entry of vehicle information
- Selection of testing mode
- Test control conveniently in the vehicle cabin
- Usage of own tablet devices
- Same representation as on the workshop PC monitor

Easy control from the inside of the truck

- Intuitive and guided: fully automated procedure (covers 80 % of the common test ingrutines) incl. archiving and printing of the measured values

- Integrated remote control
- State of the braking test and important measuring results always at a glance

Download at play.google.com and use the app for free of charge for a 30 days testing period

Connected Repair for networked truck systems

- Brake testing
- Headlight testing
- Emission analysis
- Air condition service

Connected Repair is able to read commercially available job data. Thanks to crosslinking, the central server-based software solution eases and accelerates the work processes of all connected test devices. Purchasing BD, the software for one work station is included within the scope of delivery.

- Installation of one PC is free of charge
- Networking of other workplaces via licence (availability at their Beissbarth dealers.)
- Available in 16 languages

Connected repair: for faster work processes with the HTD 815 headlight tester

- Tests all types of light sources (xenon, bi-xenon, LED, bi-LED, halogen) and all types of truck headlights.
- MLD 815 Matrix/DLA version for glare-free high-beam systems (DLA*, Matrix)
- With CMOS camera and integrated printer.

* Dynamic Light Assist

Hydraulic load simulation

- In line with § 29 StVZO (VkBl. 09/2011), of the German road traffic registration ordinance, Deadline 31.12.2019*
- Lifting device for load simulation (lifting height: 200 mm)
- Neatly integrated into the roller housing
- Increases the brake-cylinder pressure to the 1.7 bar demanded
- Remote control (optional) right from the driver cab
- Suitable for almost all trucks and trailers
- Especially recommended for empty/lightweight lorries

According to the guideline, commercial vehicles need to be tested with a minimum statutory brake pressure of 1.7 bar. In case of commercial vehicles with a high load/no-load ratio - e.g. empty trucks and trailers - not building up the required minimum pressure, load simulation can be used as well. Instead of sophisticated tying down of multiple axles, the axle to be tested can also be lifted for the test. At this much simpler procedure, the required axial pressure is created by altering the weight balance.

Fits in almost all popular foundations

- Easy installation
- Because the hydraulics of the load simulation is integrated in the roller set housing, it is possible install the BD in almost all old foundations. Simply remove the old test bench and use new ones.

System requirements

Min. PC requirements

- Operating system: Windows 7, Windows 10, 64 Bit

- Processor: Celeron 2.7 GHz
- Random access memory: 4 GB
- Hard disk: 500 GB
- Serial port: 2x RS232 (COM)

Min. PC display requirements (trolley)

- Size: 27"
- Solution: 1920 x 1080
- Width-to-height ratio: 16:9

Min. HDMI-TV requirements (substitute for analogue display)

- Minimum size: 40"
- Recommended size: 55"
- Solution: 1920 x 1080
- Width-to-height ratio: 16:9

Min. tablet requirements

- Operating system: Android 5.0 or higher
- Minimum size: 8"
- Recommended size: 9,6"
- Width-to-height ratio: 16:9 or 16:10
- Basic requirement: WLAN network with router

Scope of delivery

- Truck Software (part No. 1 691 810 741)
- Incl. ASA-Livestream
- Roller set left (part No. 1 691 880 520)
- Roller set right (part No. 1 691 880 521)
- Power-Box (part No. 1 691 880 372)
- Incl. 30 m cable

Configuration

| | |
|---------------|-------------------------------------|
| 1 691 810 741 | Standard-Software Truck ICperform |
| 1 691 880 520 | Roller set series 7 left |
| 1 691 880 521 | Roller set series 7 right |
| 1 691 880 372 | Power-Box Series 5 / 7 |

Technical Data

| | |
|---------------------------------|-----------|
| Max. wheel diameter | 1000 mm |
| Max. rim diameter | 32 " |
| Protection class | IP 54 |
| Length | 1300 mm |
| Height | 680 mm |
| Measuring system | - DMS |
| Width | 1040 mm |
| Coefficient of friction dry/wet | 0,8 / 0,7 |

| | |
|---------------------------------------|-----------------------|
| Roller length | 1000 mm |
| Roller elevation | 32 mm |
| Min. rim diameter | 10 " |
| Roller diameter | 205 mm |
| Min. test width | 900 mm |
| Max. test width | 2900 mm |
| Min. wheel diameter | 320 mm |
| Roller axle distance | 398 mm |
| Weight without lifting device approx. | 450 kg |
| Weight with lifting device approx. | 700 kg |
| Motor connection cable | 7 x 4 mm ² |
| Gear ratio | 1 / 16,17 |
| Test speed (low) | 2,2 km/h |
| Test speed (high) | 4,4 km/h |
| Motor revolution speed (low) | 1435 rpm |
| Motor revolution speed (high) | 2915 rpm |
| Roller revolution speed (low) | 57,6 rpm |
| Roller revolution speed (high) | 117,6 rpm |
| Motor power (low) | 2 x 6,5 kW |
| Motor power (high) | 2 x 8,5 kW |

Accessories

| | |
|---------------|--|
| 1 691 880 700 | Built-in frame BD 7xxx / 1000 mm / 13 to separated, with pit |
| 1 691 880 701 | Built-in frame BD 7xxx / 1000 mm / 13 to track width 2700 mm non-separated (w/o pit) |
| 1 691 880 702 | Built-in frame BD 7xxx / 1000 mm / 13 to track width 2800 mm non-separated (w/o pit) |
| 1 691 880 703 | Built-in frame BD 7xxx / 1000 mm / 13 to track width 2900 mm non-separated (w/o pit) |
| 1 691 810 756 | Tablet-App |
| 1 691 810 704 | IR remote control Truck |
| 1 691 810 702 | IR Kit Truck |
| 1 691 810 703 | Testlane PC with a serial interface |
| 1 691 811 250 | PC cabinet Standard empty |
| 1 691 810 743 | PC gear pack for PC cabinet Standard |
| 1 693 740 884 | Monitor holder 17 - 27" |
| 1 693 740 911 | Monitor holder 22 - 35" |
| 1 691 810 722 | Stand column aluminium RAL 7016 for TV Monitor / rectangular analog display |

| | |
|---------------|---|
| 1 691 810 723 | Pit safety PSC2 cross |
| 1 691 810 724 | Pit safety PSC2 cross |
| 1 691 810 725 | Pit safety PSC2 cross |
| 1 691 810 726 | Pit safety PSC1 long |
| 1 692 100 102 | Swivel bracket PSC1 |
| 1 691 810 733 | Wired air pressure sensor APS1 basic set - PM / PX1 |
| 1 691 810 734 | Wired pedal force tester APS1 PD |
| 1 691 810 735 | Warn-System for air pressure sensors |
| 1 691 841 007 | Side Slip Tester MSS 8400 |
| 1 691 842 001 | Built in frame for MSS 8400 |
| 1 691 850 100 | Joint play detector GST 8508 400V |
| 1 691 880 704 | Kit-Drive over plate BD 7xxx |
| 1 691 880 705 | Adaptation kit for tachograph test with proximity switch BD7xxx 13 to |
| 1 691 880 706 | Adaptation kit for Semmler Tachocontrol BD7xxx 13 to |
| 1 691 601 392 | Digital calibration kit for brake tester |
| 1 693 770 658 | Air pressure sensors Truck APS 3 |